

2020 NHDOT Qualified Asphalt Binder Suppliers List

Supplier	Contact Information	Submitted Date	Approval Date
Gorman Asphalt, Ltd. Rensselaer, NY Terminal	290 Riverside Ave. Rensselaer, NY 12144 (518) 436-1289	1/14/2020	4/7/2020
Pike Industries, Inc. Avery Lane and River Road Terminal Newington, NH	3 Eastgate Park Road Belmont, NH 03220 (603) 527-5100	1/30/2020	3/20/2020
All States Asphalt, LLC. Deerfield, MA Terminal	901 River Road East Deerfield, MA 01342 (413) 223-5023/5027	2/6/2020	3/20/2020
All States Asphalt, LLC. Albany, NY Terminal	301 Normanskill Street Albany, NY 12202 (413) 223-5023/5027	2/7/2020	3/20/2020
Irving Oil Avery Lane and River Road Terminal Newington, NH	10 King Square South, Saint John, New Brunswick, Canada, E2L 0G3 (506) 202-4856	2/18/2020	3/20/2020
Irving Oil South Portland, ME Marine Terminal	59 Main Street South Portland, ME 04106 (603) 828-8742	2/18/2020	4/7/2020
Irving Oil Everett, MA Marine Terminal	43 Beacham Street Everett, MA 02149 (603) 828-8742	2/18/2020	4/7/2020
McAsphalt Industries Limited Valleyfield Terminal	950 Cadieux Boulevard Valleyfield, Quebec J6T 6L4 (514) 645-1691	2/19/2020	5/20/2020
Peckham Asphalt Resale Corporation D.b.a.: PARCO - Athens Terminal	2 Union Street Ext. Athens, NY 12015 (518) 945-1120	2/19/2020	4/1/2020
Suncor Energy Products Partnership Montreal Refinery	11701, Sherbrooke East Montreal, Quebec, Canada, H1B 1C3 514-640-8160	3/2/2020	3/20/2020
Bitumar USA, Inc. S. Portland, ME	1 Clark Road South Portland, ME 04106	3/6/2020	4/1/2020
Bitumar Inc. Montreal, Quebec Terminal	3000 Broadway Montreal, Quebec, H1B 5B4 (514) 645-4561	3/10/2020	3/20/2020
Bitumar USA, Inc. Hudson Terminal Corporation	29 Terminal Road Providence, RI, 02905 (401) 941-0500	5/7/2020	6/18/2020

Qualified Asphalt Binder Suppliers have demonstrated, through their QC Plan submissions, that they are capable of supplying one or more PG asphalt binder grades for projects subject to NHDOT specifications. The PG asphalt binder supplied shall not be air blown or contain any form of used, recycled or re-refined oil (ex. REOB or VGO), PPA content shall be less than 1% by weight, and the “-28” low-end temperature of an asphalt binder performance grade shall be achieved with a “neat” binder only. The use of any extender to achieve the “-28” low-end temperature is not allowed. Asphalt performance grades with a “-34” low-end temperature can be achieved with an approved “neat” binder or with the use of an approved virgin aromatic oil.